

# AM-10S Activation Panel



AM-10S activation panel is used to activate alarm tones/stored messages (not Live Audio) for CS and SB series sirens. It is built in a sealed enclosure and it is connected to a siren or to a siren group on a Comtel bus up to a maximum distance 1000m via a dedicated Serial Data Cable (RS485).

<b>GENERAL SPECIFICATIONS</b>	
<b>CONSOLE</b>	
<b>Power supply</b>	Nominal 12VDC. Obtained from CS and SB series sirens.
<b>DC current consumption</b>	
<b>Stand by</b>	50mA.
<b>Operating temperature</b>	- 10° C to + 60° C.
<b>CONNECTIVITY</b>	
<b>RS485 network</b>	
<b>FEATURES</b>	
<b>Push buttons</b>	5.
<b>Power indicator</b>	Available.
<b>Activation indicator</b>	Available.
<b>Error indicator</b>	Available.
<b>Warning signals and/or stored messages</b>	Up to 5.
<b>MECHANICAL</b>	
<b>Installation</b>	Wall mounting.
<b>Dimensions</b>	222mm X 146mm X 125mm (H X W X D).
<b>Weight</b>	3kg.
<b>IP rate</b>	IP 65.
<b>CERTIFICATIONS AND APPROVALS</b>	
	CE RoHS
<b>ORDER DETAILS</b>	
<b>Basic unit</b>	1.016.010.01