

SB-1-2-100A



SB high power electronic warning siren is the new member in Comtel sirens series family. It has been designed to satisfy warning and notification needs in areas a single siren or a small siren network is required. Maintenance free (as has no motors and moving parts) can be easily installed indoor and outdoor. Powered from maintenance free VRLA or LiFePO4 rechargeable batteries which guarantees uninterrupted operation is always ready to provide optimum protection. Siren status can be monitored locally or remotely to diagnose errors and operational functionality to ensure minimal downtime and continuity of operation. A variety of interfaces and HMIs are available to customize the unit in terms of communication, activation, monitoring and management.

- On board signal generator producing up to 16 full programmable signals.
- On board 8GB SD card to store up to 239WAV 16bit voice messages.
- Radio (analog/digital).
- Transparent modem (analog/digital).
- 868MHz license free data radio.
- CMC 4 serial HMI control console.
- CMC 8 serial HMI control console.

- CMC 16 serial controller .
- AM 10 alarm activation module.
- AM 10S/RS 485 alarm activation module.
- On board GSM communication serial controller.
- Voice and data over IP card.
- Fiber optics converters.
- Data logger s/w.
- Talos LV5/LV10/FV128 management s/w.

GENERAL SPECIFICATIONS	
CONTROLLER	
Power supply	Nominal 24VDC. Obtained from 2X12V/18-26Ah Lead acid maintenance free batteries.
Batteries	Maximum capacity: 26Ah. Dimensions: 125mm X 175mm X 166mm (H X W X D).
Batteries chargers	1 X 27 VDC/240W.
Amplifiers	1 Class D 200W.
SPL	100dB @ 30m.
AC power consumption	
Stand by	3.10W.
Full charging state	240W.
DC current consumption	
Stand by	63mA.
Activated with full power	5A.
Operating temperature	- 10° C to + 60° C.
COMMUNICATION	
RS485	1 X RS485 serial port. RJ45. Connection to Comtel HMIs (RS485 [A+, B-], Audio input [A1, A2], 0VDC/12VDC). Connection to Baud rate: 1200 bps to 115200 bps.
Mini USB	For firmware update. Connection to Baud rate: 115200 bps.
Ethernet port	Integrated server ,Web browser for configuration / Programming.
RS232	1 X RS232 serial port. DB9F. Connection to radio modem.
FEATURES	
Monitor inputs	2 inputs (Dry contact). AC monitoring. Cabinet door monitoring.
Control inputs	8 configurable inputs (Dry contact/Open collector).
Control outputs	2 Relay (12VDC/1A) controlled (N.O./N.C.) output.
Warning signals	Up to 16 (fully programmable).
Stored messages	Up to 239 (fully programmable). PCM format 8bit 44.1KHz mono.
Live Audio (Public Address)	Available.
MicroSD	Alarm tones/ stored messages storage.
SPEAKER ARRAY	
Speakers	1 axial horn.
Configuration	Omni directional.
Power	100W.
Weight	6.5kg. Compression drivers included.
Mast required	2.5" galvanized.
Wind load	
MECHANICAL	
Cabinet dimensions	600mm X 500mm X 200mm (H X W X D).
Weight	36kg (batteries not included).
IP rate	IP 66 conforming to IEC 60529.
Paint	RAL 7035.
Cable glands	PG16(2x) PG21(2X) polyamide .
CERTIFICATIONS AND APPROVALS	
	CE RoHS
ORDER DETAILS	
Order code	1.025.101.04