

# CMC-4 Operation Panel



**CMC-4 Operation Panel** is a versatile HMI device for operating and interrogating CS and SB series sirens. Connection with siren can be up to a maximum distance 1000m via a dedicated Serial Data Cable (RS485). The Cmc-4 can also be connected to a VHF/UHF radio base station or other communication media equipment such as fiber optics networks.

CMC-4 provides the ability to choose a single siren or a group of sirens managed by and activate a warning signal and a voice or a pre recorded message plus the ability to perform random diagnostic control of the network. The information displayed on the LCD concern the communication between the control station and the network and the status of various systems of a siren such as battery voltages, amplifiers status, speaker array status, etc.

The small lightweight and robust body is including mounting panel for immediate integration in siren's cabinet.

<b>GENERAL SPECIFICATIONS</b>	
<b>CONSOLE</b>	
<b>Power supply</b>	Nominal 12VDC. Obtained from Comtel RS485 bus or from external power supply.
<b>DC current consumption</b>	
Stand by	30mA.
Stand by (backlight ON)	130mA.
<b>Operating temperature</b>	– 10 <sup>o</sup> C to + 60 <sup>o</sup> C.
<b>COMMUNICATION</b>	
<b>RS485</b>	1 X RS485 serial port. RJ45. Programming I/P. Connection to siren and/or communication network (RS485 [A+, B-], Audio input [A1, A2], 0VDC/12VDC). Baud rate: 1200 bps to 115200 bps.
<b>AUDIO</b>	
<b>Analog audio I/P</b>	1 X MIC input. RJ45.
<b>CONNECTIVITY</b>	
<b>RS485 network</b>	
<b>MANAGEMENT</b>	
<b>Sirens</b>	Up to 8.
<b>Sirens groups</b>	Up to 8.
<b>FEATURES</b>	
<b>Alarm tones</b>	4 alarm tones (volume controlled).
<b>Digital messages</b>	2 stored messages (volume controlled).
<b>Silent test</b>	Available for a single siren or a group of sirens.
<b>Status test</b>	Available.
<b>Live Audio (Public Address)</b>	Available (volume controlled).
<b>Recorded messages</b>	Available. A recorded message can be uploaded to a siren's memory.
<b>Access</b>	i-Button key.
<b>MECHANICAL</b>	
<b>Installation</b>	Wall mounting or inside siren's cabinet.
<b>Dimensions</b>	150mm X 110mm X 48mm (H X W X D).
<b>Weight</b>	500g.
<b>IP rate</b>	IP 44.
<b>Paint</b>	RAL 7035.
<b>CERTIFICATIONS AND APPROVALS</b>	
	CE RoHS
<b>ORDER DETAILS</b>	
<b>CMC 4 basic unit</b>	1.016.010.00
<b>Handheld microphone</b>	1.016.030.01
<b>Access key</b>	1.021.001.07